

BSA 1005 D PRIMERA



ROBUST BUILD - MINIMUM CONTROLS – MANOEUVRABLE - EASY MAINTENANCE - INCREASED PRODUCTIVITY



3 SIMPLE CONTROLS

- ENGINE SPEED CONTROL
- CONCRETE PUMP FORWARD/REVERSE
- CONCRETE PUMP ON/OFF

AUTOMATIC CENTRAL LUBRICATION

TECHNICAL DATA

<input type="checkbox"/> WATER COOLED 4 CYLINDER PERKINS DIESEL ENGINE	62 Kw
<input type="checkbox"/> MAXIMUM THEORETICAL CONCRETE PRESSURE	53 Bar
<input type="checkbox"/> MAXIMUM THEORETICAL CONCRETE OUTPUT	54 m ³ /hr
<input type="checkbox"/> DELIVERY CYLINDER DIAMETER	180 mm
<input type="checkbox"/> DELIVERY DISTANCE STROKE	1000 mm
<input type="checkbox"/> CONCRETE HOPPER CAPACITY	350 litres
<input type="checkbox"/> PUMP OUTLET DIAMETER	125 mm
<input type="checkbox"/> AUTOMATIC CENTRAL LUBRICATION	
<input type="checkbox"/> DIMENSIONS	LENGTH 4220mm : WIDTH 1540mm : HEIGHT 1900mm
	WEIGHT 2700Kg

OPTIONS

- CABLE REMOTE CONTROL
- STROKE COUNTER
- WATER PUMP

