

PK-85



BASE PORTANTE / UNDERCARRIAGE	Ancho / Alto / Largo transp. Largeur / Hauteur / Longueur de tr. Transp. Width / Height / Length Largura / Altura / Longo transp.	2.500 mm 3.620 mm 13.100 mm	
	Ancho trabajo Largeur travail Work Width Largura trabalho	3.500 mm	
	Ancho tejas Largeur tuile Track Shoes Width Largura esteira	600 mm	
	Longitud en transp. Longeur en transp. Transport length Comprimento transp.	12.000 mm	
	Peso en transp. con C.P. (sin C.P.) Poids en transp. avec C.P. (sans C.P.) Transp. weight with C.W. (without C.P.) Peso en transp. con C.P. (sem C.P.)	32,7 Tn (31,4 Tn)	
	Area de trabajo Aire de travail Working area Area de trabalho	360°	
Contrapeso telescópico Contrepoid télescopique Telescopic counter weight Contrapeso telescópico	1,35 Tn		
C.F.A.	Max. Ø	800 mm	
	Profundidad máx. / Max depth Profundidade max. / Profondeur maxi	19.000 mm	
	Tubo inyección / Injection pipe Ø	100 mm	
MOTOR MOTEUR ENGINE	CATERPILLAR C4.4 130 Kw. (174 CV) TIER 4 INTERIM CATERPILLAR C7.1 168Kw. (225 CV) TIER 3		
	Masa de rotación CFA Table de rotation Rotary head Mesa de rotação	POS / GEAR / VIT.	TORQUE
1		7.400 Kg.m	0 - 15
2		6.100 Kg.m	0 - 18
3		4.900 Kg.m	0 - 22
4			
Mástil telescópico Mât télescopique Telescopic mast Mastro telescópico	Carrera mástil telescópico Course du mât télescopique Telescopic mast stroke Carreira mastro telescópico	6.000 mm	
	Altura máx. Mastil Hauteur maxi du mât télescopique Max mast height Largura max. do mastro	23.050 mm	
	Profundidad max. telescópico cerrado Profondeur maxi telescope fermé Max. depth telescope closed Profundidade max. telescopic fechado	13.000 mm	
Inclinación mástil Inclinaison mât Mast rake Inclinação mastro	Lateral 3° + 3°	Frontal 3°	Trasera 15°
	Latérale 3° + 3°	Frontale 3°	Arrière 15°
	Side 3° + 3°	Front 3°	Back 15°
	Lateral 3° + 3°	Frontal 3°	Traseira 15°
Cabrestante principal Treuil principal Main winch Guincho principal	Tiro máx. (x2 reenvios) Capacité max. (x2 mouflage) Max. capacity (x2 falls) Capacidade max. (x2 reenvios)	26 Tn	
	Cabrestante aux. Treuil aux. Aux. winch Guincho aux.	Tiro máx. Capacité max. Max. capacity Capacidade max.	4,9 Tn
Cabrestante pull down Treuil pull down Crowd winch Guincho pull down		Tiro máx. Capacité max. Max. capacity Capacidade max.	3 Tn
	Bombas hidráulicas Pompes hydrauliques Hydraulic pumps Bombas hidráulicas	Caudal Débit Flow Fluxo	380 l/min a 350 bar 210 l/min a 350 bar
Presión sobre el suelo Pression sur le sol Pressure on the ground Pressão sobre o solo		0,80 Kg /cm²	

